

# SAFETY DATA SHEET

## 1. Product and Company Identification

<b>Product identifier</b>	<b>Blackhawk Foaming Coil Cleaner (4127-75)</b>
<b>Other means of identification</b>	Not available
<b>Recommended use</b>	Cleaner
<b>Recommended restrictions</b>	None known.
<b>Manufacturer</b>	Nu-Calgon 2008 Altom Court St. Louis, MO 63146 US

## 2. Hazards Identification

<b>Physical hazards</b>	Gases under pressure	Liquefied gas
<b>Health hazards</b>	Serious eye damage/eye irritation	Category 1
<b>Environmental hazards</b>	Not classified.	
<b>OSHA defined hazards</b>	Not classified.	

### Label elements



<b>Signal word</b>	Danger
<b>Hazard statement</b>	Contains gas under pressure; may explode if heated. Causes serious eye damage.
<b>Precautionary statement</b>	
<b>Prevention</b>	Wear eye/face protection.
<b>Response</b>	If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a poison center/doctor.
<b>Storage</b>	Protect from sunlight. Store in a well-ventilated place.
<b>Disposal</b>	Dispose of waste and residues in accordance with local authority requirements.
<b>Hazard(s) not otherwise classified (HNOC)</b>	None known.
<b>Supplemental information</b>	Not applicable.

## 3. Composition/Information on Ingredients

### Mixture

Chemical name	Common name and synonyms	CAS number	%
Butane		106-97-8	2.95
Propane		74-98-6	2.05
Diethylene glycol monoethyl ether		111-90-0	2
Ethanol, 2-butoxy-		111-76-2	2
Sodium lauryl sulfate		151-21-3	1.9
Tetrasodium ethylenediamine tetraacetate		64-02-8	1.48
Sodium metasilicate		6834-92-0	0.24

## 4. First Aid Measures

<b>Inhalation</b>	If symptoms develop move victim to fresh air. If symptoms persist, obtain medical attention.
<b>Skin contact</b>	Flush with cool water. Wash with soap and water. Obtain medical attention if irritation persists.
<b>Eye contact</b>	If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a poison center/doctor.
<b>Ingestion</b>	In the unlikely event of swallowing contact a physician or poison control center. Rinse mouth.

<b>Most important symptoms/effects, acute and delayed</b>	Symptoms may include stinging, tearing, redness, swelling, and blurred vision.
<b>Indication of immediate medical attention and special treatment needed</b>	Provide general supportive measures and treat symptomatically.
<b>General information</b>	Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

---

## 5. Fire Fighting Measures

---

<b>Suitable extinguishing media</b>	Alcohol foam. Carbon dioxide. Dry chemical. Foam.
<b>Unsuitable extinguishing media</b>	None known.
<b>Specific hazards arising from the chemical</b>	Contents under pressure.
<b>Special protective equipment and precautions for firefighters</b>	Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.
<b>Fire-fighting equipment/instructions</b>	In case of fire: Stop leak if safe to do so. Do not move cargo or vehicle if cargo has been exposed to heat. Move containers from fire area if you can do so without risk. Use water spray to cool unopened containers. Containers should be cooled with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.
<b>Specific methods</b>	Cool containers exposed to flames with water until well after the fire is out.
<b>Hazardous combustion products</b>	May include and are not limited to: Oxides of carbon.
<b>Explosion data</b>	
<b>Sensitivity to mechanical impact</b>	Not available.
<b>Sensitivity to static discharge</b>	Not available.

---

## 6. Accidental Release Measures

---

<b>Personal precautions, protective equipment and emergency procedures</b>	Keep unnecessary personnel away. Keep out of low areas. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
<b>Methods and materials for containment and cleaning up</b>	Refer to attached safety data sheets and/or instructions for use. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. This product is miscible in water. Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Isolate area until gas has dispersed. Prevent entry into waterways, sewer, basements or confined areas. Following product recovery, flush area with water. For waste disposal, see section 13 of the SDS.
<b>Environmental precautions</b>	Avoid discharge into drains, water courses or onto the ground.

---

## 7. Handling and Storage

---

<b>Precautions for safe handling</b>	Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. Do not get this material in contact with eyes. Do not get this material in contact with skin. Avoid prolonged exposure. Use only in well-ventilated areas. Wear appropriate personal protective equipment.
<b>Conditions for safe storage, including any incompatibilities</b>	Contents under pressure. Do not expose to heat or store at temperatures above 120°F/49°C as can may burst. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. Store in a cool, dry place out of direct sunlight. Store in a well-ventilated place. Store away from incompatible materials (see Section 10 of the SDS).

---

## 8. Exposure Controls/Personal Protection

---

### Occupational exposure limits

#### US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value
Ethanol, 2-butoxy- (CAS 111-76-2)	PEL	240 mg/m3
		50 ppm
Propane (CAS 74-98-6)	PEL	1800 mg/m3

**US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)**

Components	Type	Value
		1000 ppm

**US. ACGIH Threshold Limit Values**

Components	Type	Value
Butane (CAS 106-97-8)	STEL	1000 ppm
Ethanol, 2-butoxy- (CAS 111-76-2)	TWA	20 ppm

**US. NIOSH: Pocket Guide to Chemical Hazards**

Components	Type	Value
Butane (CAS 106-97-8)	TWA	1900 mg/m3
		800 ppm
Ethanol, 2-butoxy- (CAS 111-76-2)	TWA	24 mg/m3
		5 ppm
Propane (CAS 74-98-6)	TWA	1800 mg/m3
		1000 ppm

**US. AIHA Workplace Environmental Exposure Level (WEEL) Guides**

Components	Type	Value
Diethylene glycol monoethyl ether (CAS 111-90-0)	TWA	140 mg/m3
		25 ppm

**Biological limit values**

**ACGIH Biological Exposure Indices**

Components	Value	Determinant	Specimen	Sampling Time
Ethanol, 2-butoxy- (CAS 111-76-2)	200 mg/g	Butoxyacetic acid (BAA), with hydrolysis	Creatinine in urine	*

\* - For sampling details, please see the source document.

**Appropriate engineering controls**

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

**Individual protection measures, such as personal protective equipment**

<b>Eye/face protection</b>	Chemical splash goggles.
<b>Skin protection</b>	
<b>Hand protection</b>	Wear protective gloves.
<b>Other</b>	Not available.
<b>Respiratory protection</b>	Wear positive pressure self-contained breathing apparatus (SCBA).
<b>Thermal hazards</b>	Not applicable.

**General hygiene considerations**

When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

**9. Physical and Chemical Properties**

<b>Appearance</b>	Compressed liquefied gas
<b>Physical state</b>	Gas.
<b>Form</b>	Liquefied gas.
<b>Color</b>	Clear
<b>Odor</b>	Lemon lime
<b>Odor threshold</b>	Not available.
<b>pH</b>	12.3
<b>Melting point/freezing point</b>	Not available.

<b>Initial boiling point and boiling range</b>	32 - 401 °F (0 - 205 °C)
<b>Pour point</b>	Not available.
<b>Specific gravity</b>	Not available.
<b>Partition coefficient (n-octanol/water)</b>	Not available
<b>Flash point</b>	Not available.
<b>Evaporation rate</b>	Not available
<b>Flammability (solid, gas)</b>	Not applicable.
<b>Upper/lower flammability or explosive limits</b>	
<b>Flammability limit - lower (%)</b>	Not available.
<b>Flammability limit - upper (%)</b>	Not available.
<b>Explosive limit - lower (%)</b>	Not available.
<b>Explosive limit - upper (%)</b>	Not available.
<b>Vapor pressure</b>	65 psi @ 70°F
<b>Vapor density</b>	Not available
<b>Relative density</b>	Not available.
<b>Solubility(ies)</b>	Not available <b>Auto-ignition temperature</b> Not available
<b>Decomposition temperature</b>	Not available.
<b>Viscosity</b>	Not available.
<b>Other information</b>	
<b>Flash point class</b>	Not Flammable as per testing under UN Manual of Tests and Criteria Part 3, Section 31.5

---

## 10. Stability and Reactivity

---

<b>Reactivity</b>	Reacts vigorously with acids.
<b>Possibility of hazardous reactions</b>	No dangerous reaction known under conditions of normal use.
<b>Chemical stability</b>	Material is stable under normal conditions.
<b>Conditions to avoid</b>	Reacts violently with strong acids. This product may react with oxidizing agents. Do not mix with other chemicals. Contact with incompatible materials.
<b>Incompatible materials</b>	Not corrosive to SAE 1020 Steel or non-clad Aluminum based on test data (UN Manual of Tests and Criteria, Part III, Section 37.1 -Corrosion to metals).  Oxidizing agents. Acids.
<b>Hazardous decomposition products</b>	May include and are not limited to: Oxides of carbon.

---

## 11. Toxicological Information

---

<b>Routes of exposure</b>	Inhalation. Ingestion. Skin contact. Eye contact.
<b>Information on likely routes of exposure</b>	
<b>Ingestion</b>	Expected to be a low ingestion hazard.
<b>Inhalation</b>	Prolonged inhalation may be harmful.
<b>Skin contact</b>	US GHS: Not corrosive to skin based on in-vitro test data (OECD Guideline 435 - Corrositex®).  CANADA WHMIS: As per Policy Issue Sheet Number 60, strongly acidic or alkaline substances with a demonstrated pH of 2 or less or 11.5 or greater, need not be tested for primary dermal irritation, owing to their predictable corrosive properties.
<b>US. NIOSH: Pocket Guide to Chemical Hazards</b>	
Ethanol, 2-butoxy- (CAS 111-76-2)	Can be absorbed through the skin.
<b>Eye contact</b>	Causes serious eye damage.
<b>Symptoms related to the physical, chemical and toxicological characteristics</b>	Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including blindness could result.
<b>Information on toxicological effects</b>	
<b>Acute toxicity</b>	

Components	Species	Test Results
Butane (CAS 106-97-8)		
<b>Acute</b>		
<i>Inhalation</i>		
LC50	Mouse	680 mg/l, 2 Hours
	Rat	276000 ppm, 4 Hours
		658 mg/l/4h
<i>Oral</i>		
LD50	Not available	
Diethylene glycol monoethyl ether (CAS 111-90-0)		
<b>Acute</b>		
<i>Dermal</i>		
LD50	Guinea pig	5900 mg/kg
	Mouse	6000 mg/kg
	Rabbit	6000 mg/kg
	Rat	6000 mg/kg
<i>Inhalation</i>		
LC50		
	Rat	5240 mg/l/4h
<i>Oral</i>		
LD50	Guinea pig	3000 mg/kg
	Rabbit	3620 mg/kg
	Rat	5500 mg/kg
		1920 mg/kg
Ethanol, 2-butoxy- (CAS 111-76-2)		
<b>Acute</b>		
<i>Dermal</i>		
LD50	Guinea pig	207 mg/kg
	Rabbit	400 mg/kg
		220 mg/kg
		99 mg/kg
	Rat	99 mg/kg
<i>Inhalation</i>		
LC50	Mouse	700 ppm, 7 Hours
	Rat	450 ppm, 4 Hours
		2.2 mg/l, 4 Hours
<i>Oral</i>		
LD50	Guinea pig	1200 mg/kg
	Mouse	1200 mg/kg
	Rabbit	320 mg/kg
	Rat	470 mg/kg
Propane (CAS 74-98-6)		
<b>Acute</b>		
<i>Inhalation</i>		
LC50	Rat	> 1442.8 mg/l, 15 Minutes
<i>Oral</i>		
LD50	Not available	
Sodium lauryl sulfate (CAS 151-21-3)		
<b>Acute</b>		
<i>Dermal</i>		
LD50	Rabbit	580 mg/kg

Components	Species	Test Results
<i>Inhalation</i> LC50	Rat	> 3900 mg/m3, 1 hr
<i>Oral</i> LD50	Rat	1288 mg/kg
Sodium metasilicate (CAS 6834-92-0)		
<b>Acute</b>		
<i>Dermal</i> LD50	Not available	
<i>Inhalation</i> LC50	Not available	
<i>Oral</i> LD50	Mouse	2400 mg/kg
	Rat	1153 mg/kg
Tetrasodium ethylenediamine tetraacetate (CAS 64-02-8)		
<b>Acute</b>		
<i>Dermal</i> LD50	Not available	
<i>Inhalation</i> LC50	Not available	
<i>Oral</i> LD50	Rat	1658 mg/kg
<b>Skin corrosion/irritation</b>	US GHS: Not corrosive to skin based on in-vitro test data (OECD Guideline 435 - Corrositex®).	
	CANADA WHMIS: As per Policy Issue Sheet Number 60, strongly acidic or alkaline substances with a demonstrated pH of 2 or less or 11.5 or greater, need not be tested for primary dermal irritation, owing to their predictable corrosive properties.	
<b>Exposure minutes</b>	Not available.	
<b>Erythema value</b>	Not available.	
<b>Oedema value</b>	Not available.	
<b>Serious eye damage/eye irritation</b>	Causes serious eye damage.	
<b>Corneal opacity value</b>	Not available.	
<b>Iris lesion value</b>	Not available.	
<b>Conjunctival reddening value</b>	Not available.	
<b>Conjunctival oedema value</b>	Not available.	
<b>Recover days</b>	Not available.	
<b>Respiratory or skin sensitization</b>		
<b>Respiratory sensitization</b>	Not available.	
<b>Skin sensitization</b>	This product is not expected to cause skin sensitization.	
<b>US. NIOSH: Pocket Guide to Chemical Hazards</b>		
Ethanol, 2-butoxy- (CAS 111-76-2)	Can be absorbed through the skin.	
<b>US. NIOSH: Pocket Guide to Chemical Hazards</b>		
Ethanol, 2-butoxy- (CAS 111-76-2)	Can be absorbed through the skin.	
<b>Germ cell mutagenicity</b>	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.	
<b>Mutagenicity</b>	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.	
<b>Carcinogenicity</b>	This product is not considered to be a carcinogen by IARC, NTP, or OSHA.	
<b>ACGIH Carcinogens</b>		
Ethanol, 2-butoxy- (CAS 111-76-2)	A3 Confirmed animal carcinogen with unknown relevance to humans.	
<b>IARC Monographs. Overall Evaluation of Carcinogenicity</b>		
Ethanol, 2-butoxy- (CAS 111-76-2)	Volume 88 - 3 Not classifiable as to carcinogenicity to humans.	
<b>Reproductive toxicity</b>	This product is not expected to cause reproductive or developmental effects.	
<b>Teratogenicity</b>	Not available.	

<b>Specific target organ toxicity - single exposure</b>	Not classified.
<b>Specific target organ toxicity - repeated exposure</b>	Not classified.
<b>Aspiration hazard</b>	Not likely, due to the form of the product.
<b>Chronic effects</b>	Prolonged inhalation may be harmful.
<b>Further information</b>	Not available.
<b>Name of Toxicologically Synergistic Products</b>	Not available.

---

## 12. Ecological Information

---

<b>Ecotoxicity</b>	See below		
<b>Components</b>		<b>Species</b>	<b>Test Results</b>
Diethylene glycol monoethyl ether (CAS 111-90-0)			
Crustacea	EC50	Daphnia	4305 mg/L, 48 Hours
<b>Aquatic</b>			
Fish	LC50	Bluegill ( <i>Lepomis macrochirus</i> )	> 10000 mg/l, 96 hours
Ethanol, 2-butoxy- (CAS 111-76-2)			
Crustacea	EC50	Daphnia	1819 mg/L, 48 Hours
<b>Aquatic</b>			
Fish	LC50	Inland silverside ( <i>Menidia beryllina</i> )	1250 mg/l, 96 hours
Sodium lauryl sulfate (CAS 151-21-3)			
Algae	IC50	Algae	53 mg/L, 72 Hours
Crustacea	EC50	Daphnia	1.8 mg/L, 48 Hours
<b>Aquatic</b>			
Fish	LC50	Carp, hawk fish ( <i>Cirrhinus mrigala</i> )	1.36 mg/l, 96 hours
Sodium metasilicate (CAS 6834-92-0)			
<b>Aquatic</b>			
Crustacea	EC50	Water flea ( <i>Ceriodaphnia dubia</i> )	0.28 - 0.57 mg/l, 48 hours
Fish	LC50	Western mosquitofish ( <i>Gambusia affinis</i> )	1800 mg/l, 96 hours
Tetrasodium ethylenediamine tetraacetate (CAS 64-02-8)			
Algae	EC50	Algae	1.01 mg/L, 72 Hours
<b>Aquatic</b>			
Crustacea	EC50	Water flea ( <i>Daphnia magna</i> )	610 mg/l, 24 hours
Fish	LC50	Bluegill ( <i>Lepomis macrochirus</i> )	472 - 500 mg/l, 96 hours
<b>Persistence and degradability</b>	No data is available on the degradability of this product.		
<b>Bioaccumulative potential</b>	No data available.		
<b>Mobility in soil</b>	No data available.		
<b>Mobility in general</b>	Not available.		
<b>Other adverse effects</b>	No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.		

---

## 13. Disposal Considerations

---

<b>Disposal instructions</b>	Consult authorities before disposal. Contents under pressure. Do not puncture, incinerate or crush. This material and its container must be disposed of as hazardous waste. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international regulations.
<b>Local disposal regulations</b>	Dispose in accordance with all applicable regulations.
<b>Hazardous waste code</b>	The waste code should be assigned in discussion between the user, the producer and the waste disposal company.
<b>Waste from residues / unused products</b>	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
<b>Contaminated packaging</b>	Empty containers should be taken to an approved waste handling site for recycling or disposal. Since emptied containers may retain product residue, follow label warnings even after container is emptied. Do not re-use empty containers.

---

## 14. Transport Information

---

### U.S. Department of Transportation (DOT)

#### Basic shipping requirements:

UN number	UN1950
Proper shipping name	Aerosols, non-flammable, (each not exceeding 1 L capacity)
Hazard class	Limited Quantity - US
Packaging exceptions	306
Packaging non bulk	None
Packaging bulk	None

### Transportation of Dangerous Goods (TDG - Canada)

#### Basic shipping requirements:

UN number	UN1950
Proper shipping name	AEROSOLS, non-flammable
Hazard class	Limited Quantity - Canada
Special provisions	80

### IATA/ICAO (Air)

#### Basic shipping requirements:


UN number	UN1950
Proper shipping name	Aerosols, non-flammable
Hazard class	Limited Quantity - IATA
ERG code	2L

### IMDG (Marine Transport)

#### Basic shipping requirements:

UN number	UN1950
Proper shipping name	AEROSOLS
Hazard class	Limited Quantity - US

### DOT; IMDG; TDG



### IATA



---

## 15. Regulatory Information

---

**Canadian federal regulations** This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the SDS contains all the information required by the Controlled Products Regulations.

#### Canada CEPA Schedule I: Listed substance

Ethanol, 2-butoxy- (CAS 111-76-2) Listed.

#### Canada DSL Challenge Substances: Listed substance

Butane (CAS 106-97-8) Listed.

#### Canada NPRI VOCs with Additional Reporting Requirements: Mass reporting threshold/Identification Number

Butane (CAS 106-97-8) 1 TONNES

Ethanol, 2-butoxy- (CAS 111-76-2) 1 TONNES

Propane (CAS 74-98-6) 1 TONNES

#### Canada Priority Substances List (Second List): Listed substance

Ethanol, 2-butoxy- (CAS 111-76-2) Listed.



**Canada WHMIS Ingredient Disclosure: Threshold limits**

Butane (CAS 106-97-8)	1 %
Diethylene glycol monoethyl ether (CAS 111-90-0)	1 %
Ethanol, 2-butoxy- (CAS 111-76-2)	1 %
Sodium lauryl sulfate (CAS 151-21-3)	1 %
Sodium metasilicate (CAS 6834-92-0)	1 %

**WHMIS status** Controlled**WHMIS classification** Class A - Compressed Gas, Class E - Corrosive Material**WHMIS labeling****US federal regulations** This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.**US EPCRA (SARA Title III) Section 313 - Toxic Chemical: De minimis concentration**

Diethylene glycol monoethyl ether (CAS 111-90-0)	1.0 % N230
Ethanol, 2-butoxy- (CAS 111-76-2)	1.0 % N230

**US EPCRA (SARA Title III) Section 313 - Toxic Chemical: Listed substance**

Diethylene glycol monoethyl ether (CAS 111-90-0)	Listed. N230
Ethanol, 2-butoxy- (CAS 111-76-2)	Listed. N230

**TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)**

Not regulated.

**CERCLA Hazardous Substance List (40 CFR 302.4)**

Butane (CAS 106-97-8)	Listed.
Diethylene glycol monoethyl ether (CAS 111-90-0)	Listed.
Ethanol, 2-butoxy- (CAS 111-76-2)	Listed.
Propane (CAS 74-98-6)	Listed.

**US CAA Section 111 Volatile Organic Compounds: Listed substance**

Diethylene glycol monoethyl ether (CAS 111-90-0)	Listed.
Ethanol, 2-butoxy- (CAS 111-76-2)	Listed.

**US CAA Section 112(r) Accidental Release Prevention - Regulated Flammable Substance: Listed substance**

Butane (CAS 106-97-8)	Regulated flammable substance.
Propane (CAS 74-98-6)	Regulated flammable substance.

**US CAA Section 112(r) Accidental Release Prevention: Threshold quantity**

Butane (CAS 106-97-8)	10000 LBS
Propane (CAS 74-98-6)	10000 LBS

**Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)**

Butane (CAS 106-97-8)	Listed.
Propane (CAS 74-98-6)	Listed.

**Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List**

Diethylene glycol monoethyl ether (CAS 111-90-0)	Listed.
--	---------

**US CAA Section 612 SNAP Program: Listed substance**

Butane (CAS 106-97-8)	Listed.
Propane (CAS 74-98-6)	Listed.

**Superfund Amendments and Reauthorization Act of 1986 (SARA)**

**Hazard categories**  
 Immediate Hazard - Yes  
 Delayed Hazard - No  
 Fire Hazard - No  
 Pressure Hazard - Yes  
 Reactivity Hazard - No

**SARA 302 Extremely hazardous substance** No**SARA 311/312 Hazardous chemical** No**SARA 313 (TRI reporting)**

Chemical name	CAS number	% by wt.
Diethylene glycol monoethyl ether	111-90-0	2
Ethanol, 2-butoxy-	111-76-2	2

**Other federal regulations**

**Clean Water Act (CWA) Section 112(r) (40 CFR 68.130)** Hazardous substance

Safe Drinking Water Act (SDWA) Not regulated.

Food and Drug Administration (FDA) Not regulated.

US state regulations See below

**US - California Hazardous Substances (Director's): Listed substance**

Butane (CAS 106-97-8) Listed.  
Ethanol, 2-butoxy- (CAS 111-76-2) Listed.

**US - California Proposition 65 - Carcinogens & Reproductive Toxicity (CRT): Listed substance**

Formaldehyde (CAS 50-00-0) Listed.

**US - Illinois Chemical Safety Act: Listed substance**

Butane (CAS 106-97-8) Listed.  
Diethylene glycol monoethyl ether (CAS 111-90-0) Listed.  
Ethanol, 2-butoxy- (CAS 111-76-2) Listed.  
Propane (CAS 74-98-6) Listed.

**US - Louisiana Spill Reporting List: Reportable quantity (total mass into atmosphere)**

Diethylene glycol monoethyl ether (CAS 111-90-0) 100 LBS  
Ethanol, 2-butoxy- (CAS 111-76-2) 100 LBS

**US - Louisiana Spill Reporting: Listed substance**

Butane (CAS 106-97-8) Listed.  
Diethylene glycol monoethyl ether (CAS 111-90-0) Listed.  
Ethanol, 2-butoxy- (CAS 111-76-2) Listed.  
Propane (CAS 74-98-6) Listed.

**US - Minnesota Haz Subs: Listed substance**

Butane (CAS 106-97-8) Listed.  
Diethylene glycol monoethyl ether (CAS 111-90-0) Listed.  
Ethanol, 2-butoxy- (CAS 111-76-2) Listed.  
Propane (CAS 74-98-6) Listed.

**US - New Jersey RTK - Substances: Listed substance**

Butane (CAS 106-97-8) Listed.  
Diethylene glycol monoethyl ether (CAS 111-90-0) Listed.  
Ethanol, 2-butoxy- (CAS 111-76-2) Listed.  
Propane (CAS 74-98-6) Listed.

**US - Texas Effects Screening Levels: Listed substance**

Butane (CAS 106-97-8) Listed.  
Diethylene glycol monoethyl ether (CAS 111-90-0) Listed.  
Ethanol, 2-butoxy- (CAS 111-76-2) Listed.  
Propane (CAS 74-98-6) Listed.  
Sodium lauryl sulfate (CAS 151-21-3) Listed.  
Sodium metasilicate (CAS 6834-92-0) Listed.  
Tetrasodium ethylenediamine tetraacetate (CAS 64-02-8) Listed.

**US. Massachusetts RTK - Substance List**

Butane (CAS 106-97-8) Listed.  
Ethanol, 2-butoxy- (CAS 111-76-2) Listed.  
Propane (CAS 74-98-6) Listed.

**US. Pennsylvania RTK - Hazardous Substances**

Butane (CAS 106-97-8) Listed.  
Diethylene glycol monoethyl ether (CAS 111-90-0) Listed.  
Ethanol, 2-butoxy- (CAS 111-76-2) Listed.  
Propane (CAS 74-98-6) Listed.

**US. Rhode Island RTK**

Butane (CAS 106-97-8) Listed.  
Diethylene glycol monoethyl ether (CAS 111-90-0) Listed.  
Ethanol, 2-butoxy- (CAS 111-76-2) Listed.  
Propane (CAS 74-98-6) Listed.

**Inventory status**


Country(s) or region	Inventory name	On inventory (yes/no)*
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

\*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

## 16. Other Information

LEGEND	
Severe	4
Serious	3
Moderate	2
Slight	1
Minimal	0

HEALTH	/	2
FLAMMABILITY		1
PHYSICAL HAZARD		0
PERSONAL PROTECTION		X



### Disclaimer

The information in the sheet was written based on the best knowledge and experience currently available. Information contained herein was obtained from sources considered technically accurate and reliable. While every effort has been made to ensure full disclosure of product hazards, in some cases data is not available and is so stated. Since conditions of actual product use are beyond control of the supplier, it is assumed that users of this material have been fully trained according to the requirements of all applicable legislation and regulatory instruments. No warranty, expressed or implied, is made and supplier will not be liable for any losses, injuries or consequential damages which may result from the use of or reliance on any information contained in this document.

### Issue date

30-October-2014

### Effective date

31-October-2014

### Expiry date

31-October-2017

### Further information

For an updated SDS, please contact the supplier/manufacturer listed on the first page of the document.

### Prepared by

Nu-Calgon Technical Service Phone: (314) 469-7000

### Other information

This Safety Data Sheet was prepared to comply with the current OSHA Hazard Communication Standard (HCS) adoption of the Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

For an updated SDS, please contact the supplier/manufacturer listed on the first page of the document.