



# Material Safety Data Sheet

## Section 1: Product & Company Identification

**Product Name:** 3-36® Multi-Purpose Lubricant and Corrosion Inhibitor (aerosol)

**Product Number (s):** 03004, 03005, 03093, 83005

**Manufactured By:**

CRC Industries, Inc.  
885 Louis Drive  
Warminster, PA 18974  
[www.crcindustries.com](http://www.crcindustries.com)

General Information	(215) 674-4300
Technical Assistance	(800) 521-3168
Customer Service	(800) 272-4620
24-Hr Emergency (CHEMTREC)	(800) 424-9300

## Section 2: Hazards Identification

### Emergency Overview

Appearance & Odor: Clear blue-green liquid, pleasant odor

### DANGER

Flammable. Harmful or Fatal if Swallowed. Contents Under Pressure.

### Potential Health Effects:

- EYE:** Contact may cause mild irritation including stinging, watering and redness.
- SKIN:** Contact may cause redness, itching, burning and skin damage. Prolonged or repeated contact can worsen irritation and lead to dermatitis. No harmful effects from skin absorption are expected.
- INHALATION:** Expected to have a low degree of toxicity by inhalation. High concentrations of vapors may be irritating to the respiratory tract, and may cause headaches, dizziness, anesthesia, drowsiness, and other central nervous system effects.
- INGESTION:** Small amounts of this product aspirated into the respiratory system during ingestion or vomiting may cause mild to severe pulmonary injury, possibly progressing to death.
- CHRONIC EFFECTS:** None known
- TARGET ORGANS:** None known

Medical Conditions Aggravated by Exposure:

pre-existing dermatitis

See Section 11 for toxicology and carcinogenicity information on product ingredients.

**Product Name: 3-36® Multi-Purpose Lubricant and Corrosion Inhibitor (Aerosol)**  
**Product Number (s): 03004, 03005, 03093, 83005**

---

### **Section 3: Composition/Information on Ingredients**

<b>COMPONENT</b>	<b>CAS NUMBER</b>	<b>% by Wt.</b>
Hydrotreated light distillates	64742-47-8	65 - 75
Solvent-refined heavy paraffinic distillates	64741-88-4	15 – 25
Inhibitor blend	proprietary	5 - 15
Carbon dioxide	124-38-9	1 - 5

---

### **Section 4: First Aid Measures**

**Eye Contact:** Immediately flush with plenty of water for 15 minutes. Call a physician if irritation persists.

**Skin Contact:** Remove contaminated clothing and wash affected area with soap and water. Call a physician if irritation persists. Wash contaminated clothing prior to re-use.

**Inhalation:** Remove person to fresh air. Keep person calm. If not breathing, give artificial respiration. If breathing is difficult give oxygen. Call a physician.

**Ingestion:** If swallowed, do NOT induce vomiting. Keep at rest. Get prompt medical attention.

*Note to Physicians:* This product is an aspiration hazard.

---

### **Section 5: Fire-Fighting Measures**

Flammable Properties: This product is flammable in accordance with aerosol flammability definitions (16 CFR 1500.3(c)(6) ).

Flash Point:	170 F (TCC)	Upper Explosive Limit:	5.0
Autoignition Temperature:	ND	Lower Explosive Limit:	0.7

**Suitable Extinguishing Media:** Foam, dry chemical, carbon dioxide or water spray.

**Products of Combustion:** Oxides of carbon

**Protection of Fire-Fighters:** Firefighters should wear self-contained, NIOSH-approved breathing apparatus for protection against suffocation and possible toxic decomposition products. Proper eye and skin protection should be provided. Use water spray to keep fire-exposed containers cool and to knock down vapors which may result from product decomposition.

---

### **Section 6: Accidental Release Measures**

**Personal Precautions:** Use personal protection recommended in Section 8.

**Environmental Precautions:** Take precautions to prevent contamination of ground and surface waters. Do not flush

**Product Name: 3-36® Multi-Purpose Lubricant and Corrosion Inhibitor (Aerosol)**

**Product Number (s): 03004, 03005, 03093, 83005**

into sewers or storm drains.

Methods for Containment & Clean-up: Remove sources of ignition. Dike area to contain spill. Ventilate the area with fresh air. If in confined space or limited air circulation area, clean-up workers should wear appropriate respiratory protection. Recover or absorb spilled material using an absorbent designed for chemical spills. Place used absorbents into proper waste containers.

---

**Section 7: Handling and Storage**

Handling Procedures: Do not use near an open flame, heat or other sources of ignition.

Storage Procedures: Store in a cool dry area out of direct sunlight. Aerosol cans must be maintained below 120 F to prevent cans from rupturing.

Aerosol Storage Level: III

---

**Section 8: Exposure Controls/Personal Protection**

Exposure Guidelines:

COMPONENT	OSHA		ACGIH		OTHER		UNIT
	TWA	STEL	TWA	STEL	TWA	SOURCE	
Hydrotreated light distillates	NE	NE	NE	NE	1200	mfr	mg/m <sup>3</sup>
Solvent-refined heavy paraffinic distillates	5*	NE	5*	10*	NE		mg/m <sup>3</sup>
Inhibitor blend	NE	NE	NE	NE	NE		
Carbon dioxide	5000	30000(v)	5000	30,000	NE		ppm
N.E. – Not Established (c) – ceiling (s) – skin (v) – vacated *- oil mist							

Engineering Controls: Area should have ventilation to provide fresh air. Local exhaust ventilation is generally preferred because it can control the emissions of the contaminant at the source, preventing dispersion into the general work area. Use mechanical means if necessary to maintain vapor levels below the exposure guidelines. If working in a confined space, follow applicable OSHA regulations.

Respiratory Protection: None required for normal work where adequate ventilation is provided. If engineering controls are not feasible or if exposure exceeds the applicable exposure limits, use a NIOSH-approved cartridge respirator with organic vapor cartridge. Use a self-contained breathing apparatus in confined spaces and for emergencies.

Eye/face Protection: For normal conditions, wear safety glasses. Where there is reasonable probability of liquid contact, wear splash-proof goggles.

Skin Protection: Use protective gloves such as nitrile or neoprene. Also, use full protective clothing if there is prolonged or repeated contact of liquid with skin.

---

**Section 9: Physical and Chemical Properties**

Physical State: Liquid

Color: Blue-green

**Product Name: 3-36® Multi-Purpose Lubricant and Corrosion Inhibitor (Aerosol)**

**Product Number (s): 03004, 03005, 03093, 83005**

---

Odor: Pleasant

Specific Gravity: 0.8187

Initial Boiling Point: 380 F

Freezing Point: ND

Vapor Pressure: ND

Vapor Density: > 1 (air = 1)

Evaporation Rate: ND (butyl acetate = 1)

Solubility: negligible in water

pH: NA

Volatile Organic Compounds: wt %: 39.1                      g/L: 320.1                      lbs./gal: 2.67

---

**Section 10: Stability and Reactivity**

Stability: Stable

Conditions to Avoid: Temperature extremes, sources of ignition

Incompatible Materials: Strong oxidizing agents

Hazardous Decomposition Products: Oxides of carbon, oxides of sulfur, hydrocarbons

Possibility of Hazardous Reactions: No

---

**Section 11: Toxicological Information**

Long-term toxicological studies have not been conducted for this product. The following information is available for components of this product.

**ACUTE EFFECTS**

<u>Component</u>	<u>Test</u>	<u>Result</u>	<u>Route</u>	<u>Species</u>
Hydrotreated light distillate	LD50	> 5 g/kg	Oral	Rat
Hydrotreated light distillate	LD50	> 2 g/kg	Dermal	Rabbit
Hydrotreated light distillate	LC50	> 5 mg/L/4H	Inhalation	Rat

**CHRONIC EFFECTS**

Carcinogenicity:

	<u>Component</u>	<u>Result</u>
OSHA:	None listed	
IARC:	None listed	
NTP:	None listed	

Other: Paraffinic distillates                      Product testing using IP 346 shows a DMSO PAH content of < 3% by weight.

---

**Section 12: Ecological Information**

Ecological studies have not been conducted for this product. The following information is available for components of this product.

Ecotoxicity: No information available

**Product Name: 3-36® Multi-Purpose Lubricant and Corrosion Inhibitor (Aerosol)**

**Product Number (s): 03004, 03005, 03093, 83005**

Persistence / Degradability: No information available

Bioaccumulation / Accumulation: No information available

Mobility in Environment: No information available

---

---

### **Section 13: Disposal Considerations**

Disposal: The dispensed liquid product is not a RCRA hazardous waste. (See 40 CFR Part 261.20 – 261.33)  
Aerosol containers should be fully emptied and depressurized before disposal. The empty container can be recycled.

All disposal activities must comply with federal, state and local regulations. Local regulations may be more stringent than state or national requirements.

---

---

### **Section 14: Transport Information**

Proper shipping description:

US DOT (ground): Consumer Commodity, ORM-D

Special Provisions: None

---

---

### **Section 15: Regulatory Information**

#### **U.S. Federal**

#### Toxic Substances Control Act (TSCA):

All ingredients are either listed on the TSCA inventory or are exempt.

#### Comprehensive Environmental Response, Compensation and Liability Act (CERCLA):

Reportable Quantities (RQ's) exist for the following ingredients: None

**Spills or releases resulting in the loss of any ingredient at or above its RQ require immediate notification to the National Response Center (800-424-8802) and to your Local Emergency Planning Committee.**

#### Superfund Amendments Reauthorization Act (SARA) Title III:

Section 302 Extremely Hazardous Substances (EHS): None

Section 311/312 Hazard Categories:	Fire Hazard	Yes
	Reactive Hazard	No
	Release of Pressure	Yes
	Acute Health Hazard	Yes
	Chronic Health Hazard	No

Section 313 Toxic Chemicals: This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372:  
None

#### Clean Air Act:

Section 112 Hazardous Air Pollutants (HAPs): None

**Product Name: 3-36® Multi-Purpose Lubricant and Corrosion Inhibitor (Aerosol)**  
**Product Number (s): 03004, 03005, 03093, 83005**

---

Occupational Safety and Health Administration (OSHA):

This product is regulated under the Hazard Communication Standard.

**State Regulations**

California Safe Drinking Water and Toxic Enforcement Act (Prop 65):

This product may contain the following chemicals known to the state of California to cause cancer, birth defects or other reproductive harm: NONE

State Right to Know:

New Jersey: None  
Pennsylvania: None  
Massachusetts: None  
Rhode Island : None

**Additional Regulatory Information:** In states with Consumer Products VOC regulations, this product is compliant as a Multi-Purpose Lubricant.

---

**Section 16: Other Information**

NFPA: Health: 1 Flammability: 2 Reactivity: 0  
HMIS: Health: 1 Flammability: 2 Reactivity: 0 PPE: B

Prepared By: Michelle Rudnick  
CRC #: 510C  
Revision Date: 04/09/2010

Changes since last revision: Section 15: OSHA regulations added

The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. This information is accurate to the best of CRC Industries' knowledge or obtained from sources believed by CRC to be accurate. Before using any product, read all warnings and directions on the label.

CAS:	Chemical Abstract Service	NA:	Not Applicable
ppm:	Parts per Million	ND:	Not Determined
TCC:	Tag Closed Cup	NE:	Not Established
PMCC:	Pensky-Martens Closed Cup	g/L:	grams per Liter
PPE:	Personal Protection Equipment	lbs./gal:	pounds per gallon
TWA:	Time Weighted Average	STEL:	Short Term Exposure Limit
OSHA:	Occupational Safety and Health Administration		
ACGIH	American Conference of Governmental Industrial Hygienists		
NIOSH	National Institute of Occupational Safety & Health		